

# THE PVX

## Ultrasonic Precision A-Scan Thickness Gauge

The physical size, weight, and display resolution are just a few of the benefits of the PVX

- R Adjustable square wave pulser provides the flexibility necessary for both high resolution and penetration requirements.
- R Selectable viewing options provide the user with additional flexibility during operation: (RF waveform, +/- Rectified waveform, and Large Digits with Scan Bar.
- R Time based B-Scan feature displays a cross section of the test material. Displays the profile of the opposite surface of the material.
- R Adjustable resolution settings add to the PVX's flexibility.
- R Ability to use a variety of single element transducers for specific applications: Standard Delay Line (acrylic and graphite tips for metals and thin plastics), Pencil Delay Line (tough access areas on thin materials), and Contact transducers (variety of applications).
- R Hardware AGC gain control for multiple echo and thru-paint measurement.
- R Multiple calibration options: One-Point, Two-Point, or selection from a Material List.
- R 16 factory setups and 48 user-defined setups. User-defined setups can be edited for custom applications.
- R PVX is equipped with an alpha-numeric data logger to provide increased versatility for those custom reporting needs.
- R The High Speed Scan feature speeds up the inspection process by taking 32 measurements per second. Remove transducer from the test material and display the minimum measurement scanned.
- R Visual and audible alarm with Hi and Lo limit settings for specific application tolerances.
- R Auto Find feature locates the detection point(s) and adjusts the display settings to bring the waveform into view.
- R PVX comes complete with our Windows PC software for transferring data to and from a PC.
- R 2 year limited warranty.

# PVX SPECIFICATIONS

## Physical

### Size:

Width (2.5in./63.5 mm.)  
Height (6.5 in./165 mm.)  
Depth (1.24 in./31.5 mm.)

### Weight:

13.5 ounces (with batteries).

### Keyboard:

Membrane switch pad with twelve tactile keys.

### Operating Temperature:

14° to 140°F (-10°C to 60°C)

### Case:

Extruded aluminum body with nickel-plated aluminum end caps (gasket sealed).

### Data Output:

Bi-directional RS232 serial port.  
Windows® PC interface software.

### Display:

1/8in. VGA grayscale display (240 x 160 pixels). Viewable area 2.4in. x 1.8in. (62m. x 45.7mm). EL backlit (on/off/auto).

## Ultrasonic Specifications

### Measurement Modes:

Pulse-Echo (Precision—General purpose).  
Interface-Echo (Precision—Thick materials).

**Echo-Echo** (Precision—Thin materials & thru-paint).

### Pulser:

Square wave pulser with adjustable pulse width (spike, thin, wide).

### Receiver:

Manual or AGC gain control with 40dB range, depending on mode selected.

### Timing:

40 MHz with ultra low power 8 bit digitizer.

## Warranty

2 year limited



## Power Source

Three 1.5V alkaline or 1.2V NiCad AA cells.

Typically operates for 150 hours on alkaline and 100 hours on NiCad (charger not included.)

Auto power off if idle 5 min.

Battery status meter.

## Measuring

### Range:

**Interface-Echo Mode:** Steel .050in.–1.0in. (1.27mm–25.4mm).  
Plastics from .005in. (.127mm).

### Echo-Echo Mode: Steel

.006in.–.500in. (1mm–12.7mm).

### Pulse-Echo Contact: Steel

.040in.–10.0in. (1mm–254mm).  
Plastics from .010" (.254mm).

### Echo-Echo Contact: Steel

thru-paint .100in.–3.0in. (2.54mm–76.2mm).

### Resolution (selectable):

+/- .001 in. (0.01 mm)  
+/- .0001 in. (0.001 mm)

### Velocity Range:

.0492 to .5510 inches/μs  
1250 to 9999 meters/sec

One and Two Point calibration option, or selection of basic material types.

### Units:

English & Metric

## Display

### Display Views:

#### A-Scan—

Rectified +/- (half wave view)  
RF (full waveform view)

#### B-Scan—

Time based cross section view. Display speed of 15 secs per screen.

**Large Digits**—Standard thickness view. Digit Height: 0.400 in. (10mm).

**Scan Bar Thickness**—6 readings per second. Viewable in B-Scan and Large Digit views.

**Repeatability Bar Graph**—Bar graph indicates stability of reading.

## Data Logger (Internal)

12,000 readings and waveforms (alpha numeric storage).

OBSTRUCT to indicate inaccessible locations.

### Memory:

16 megabit non-volatile ram.

## Transducer

### Transducer Types:

Single Element (1 to 20 MHz).

Locking quick disconnect "00" LEMO connector.

Standard 4 foot cable.

Custom transducers and cable lengths available.

## Features:

### Setups:

16 factory and 48 custom user-defined setups.

### Gates:

Single gate in contact mode.  
Single gate with holdoff in interface-echo, echo-echo, and plastics mode. Adjustable threshold.

### Multiple Measurement Modes:

Selectable modes for use with a variety of applications.

### Alarm Mode:

Set Hi and Lo tolerances with audible beeper and visual LEDs.

### Fast Scan Mode:

Takes 32 readings per second and displays the minimum reading found when the transducer is removed. Display continuously updates while scanning.

## Certification

Factory calibration traceable to national standards.

**CHECK·LINE®**—PRECISION QUALITY CONTROL INSTRUMENTS

**Electromatic Equipment Co., Inc.**  
600 Oakland Ave.  
Cedarhurst, N Y 11516 —USA

**Tel:** (800) 645-4330 (USA & Canada)  
**Tel:** (516) 295-4300  
**Fax:** (516) 295-4399

**Email:** info@checkline.com  
**Website:** www.checkline.com

FOR ADDITIONAL INFORMATION OR TO PLACE AN ORDER CALL TOLL FREE 1-800-645-4330