Gefen W High Quality 5-Channel Speaker System For Small Spaces



Enjoy high-quality surround sound designed for your bedroom or conference room

The GefenTV CR-5SP speaker system consists of 5 exquisitely designed and tuned surround speakers which perfectly compliment the small confines of a bedroom or conference room. The CR-5SP speakers have been designed for high-quality audio fidelity rather than booming bass and high volume output. These speakers feature handsome exterior construction and will fit stylishly in a variety of decors. They come ready for wall mounting.

The Gefen CR-5SP speakers are perfectly suited to work with any audio amplifier, especially the GefenTV Audio Processor, for which they were designed.

How It Works

Simply connect the Gefen CR-5SP speakers to your amplifier. The CR-5SP speakers are equipped with 5-way binding posts having connectors as follows: bare wire, spade lug connectors, pin connectors, and two types of banana plugs (single and dual).

Once all of your AV system connections are established, set the amplifier's volume to a low level, turn on all connected AV equipment, and then increase speaker output volume to a comfortable level.

Features:

- 5-speaker surround audio from a carefully designed set of compact speakers
- Incredibly pristine sound from a compact design
- Designed to fill small rooms with high-quality sound
- · Speaker baffle naturally tilts upward on flat surfaces
- · 4-inch poly woofers with rubber surrounds
- 1-inch dome tweeter for crisp high-frequency response

Specifications:

- Woofer: 4 inch Polypropylene Black (PPB) material
- · Tweeter: 1-inch dome
- Inputs: Satin Nickel-plated 5-way binding posts
- Enclosure Type: Dual Port Vented
- Low Frequency Driver: 1 x 100mm with 25mm voice coil, Ferrite motor & Cone
- Low Frequency Driver: Pulp paper coating black & Surround NBR rubber
- High Frequency Driver: 1X 25mm with Neodymium motor & Silk dome
- High Frequency Driver: Frequency Response: (-3dB) 75Hz @ 18kHz
- High Frequency Driver: Frequency Response: (-10dB) 60Hz @ 20kHz
- High Frequency Driver: Crossover: 2.2kHz @ 2nd order LF and HF
 Rated Maximum SPL (Sound Pressure Level) Average: 99dB / Peak 105db
- Rated Maximum SPL: Long term power 30W / Short term power 50W
- System Sensitivity: (2.83V@1m) 85dB
- Nominal Impedance: 4 ohms2-Way Reflex Enclosure
- Medium Density Fiberboard Enclosure
- · Plastic frame grille with gray cloth
- · Matte White Finish
- 4 x EPDM Transparent Feet
- Dimensions: 5.7"W x 10"H x 7.2"D
- Shipping Weight: 10 lbs