

# HDMI Distributor, OHD14 / OHD18



## Descriptions

Opticis new HDMI Distributor, OHD 14 or OHD18 makes one(1) HDMI video source split into four(4) or eight(8) displays, simultaneously without any signal loss or digital noise. It guarantees to support full channels .HDMI 1.3/HDCP1.1 compliant.

## Key Features

- Offers many types of option for **EDID** (OHD14)
- Supports **DDC/HDCP**
- CEC function
- Supports up to **WUXGA (1920x1200)**, at 60Hz and HD 1080i/p (1920x1080).
- Provides status LED indicators.
- Compatible with HDMI-DVI cable.

## Technical Features

Model Name	OHD14	OHD18
Resolution	VGA to WUXGA , 480p to 1080i/p	
Input TMDs Signal	1.2V	
Input DDC Signal	5V	
Power Supply	DC +5V , 2.6A	DC +5V ,6.0A
Dimension(mm)	200 x 104 x 25	436 x 120 x 44
Weight(kg)	0.28	0.68
Operating Temp.	0℃~40℃	
Storage Temp.	-20℃ ~60℃	
Operating Humidity	30%~80%	
Storage Humidity	60%	
Power Consumption	5.5W	18W

### OPTICIS HQ

Opticis Co., Ltd.  
# 16FI, Kins Tower  
8 Sungnam-daero, 331 beon-gil,  
Bundang-gu,  
Seongnam-si, Gyunggi-do, 463-844  
South Korea  
Te I: +82 (31) 719-8033  
Fax: +82 (31) 719-8032  
tosales@opticis.com