

DVI Distributor, OVD14 / OVD18



Descriptions

Opticis new DVI Distributor, OVD 14 or OVD18 makes one(1) DVI video source split into four(4) or eight(8) DVI displays, respectively without any signal loss or digital noise. Also, HDMI source and displays are compatible by using HDMI-DVI cable.

Key Features

- Offers an **EDID** program feature
- Supports **DDC/HDCP**
- Supports up to **WUXGA (1920x1200)**, at 60Hz and HD 1080p (1920x1080).
- Provides **Power, Sync** LED indicators.
- Compatible with HDMI-DVI cable.

Technical Features

Model Name	OVD14	OVD18
Input Signal	DVI (TMDS),Single Link	DVI (TMDS),Single Link
Output Signal	DVI Single Link , 4port,	DVI Single Link , 8port
Resolution	VGA to WUXGA, 480p to 1080p	
Receptacle	DC Power Jack DVI	
Power Supply	DC +5V , 2.6A	DC +5V , 3.0A
Dimension(mm)	160 x 91 x 25	240 x 103 x 25
Weight(kg)	0.24	0.38
Operating Temp.	0°C~40°C	0°C~48°C
Storage Temp.	-20°C~45°C	
Operating Humidity	30%~80%	
Storage Humidity	60%	
Power Consumption	6W	10W

OPTICIS HQ

Opticis Co., Ltd.
304, Byucksan Technopia, 434-6 Sangdaewon-Dong, Chungwon-Ku, Sungnam City, Kyungki-Do, 462-716 South Korea
Tel: +82 (31) 737-8033~8
Fax: +82 (31) 737-8079
www.opticis.com
tosales@opticis.com