

TM-28E

TRMS AC/DC WATT Clamp Meter



CAT III 600V
 3-3/4 digit LCD, Backlit Display with maximum reading of 4000.
 High-speed bargraph.
 True-Rms.
 Watt measurement: 400KW
 Data Hold, Peak Hold, Min/Max, and Zero functions.
 AC/DC volts, AC/DC current, Resistance, Frequency, Watts, Continuity.
 Autoranging.
 Relative (REL) zero adjust.
 Maximum conductor size 35mm.
 Low battery indication.
 Overload indication.
 Continuity buzzer.
 Auto power off.

Maximum Current	600 Amps
Display	4000 counts
Max. Conductor Size	35mm
AC Current	0.1A to 600A, $\pm(2.0\%$ of rdg + 5 dgts)
AC Voltage	0.1V to 600V, $\pm(1.2\%$ of rdg + 7 dgts)
DC Current	0.1A to 600A, $\pm(1.5\%$ of rdg + 5 dgts)
DC Voltage	0.1V to 600V, $\pm(1.0\%$ of rdg + 3 dgts)
Resistance	1 Ω to 4000 Ω ,
Continuity Buzzer	Yes
Frequency	1Hz to 400KHz
AC/DC Watts	0.1W to 400KW, $\pm(5.0\%$ of rdg + 5 dgts)
Backlit Display	Yes
Autorange	Yes
High Speed Bargraph	Yes
Auto Power Off	Yes
Min/Max	Yes
REL (zero adjust)	Yes
Data Hold and Peak Hold	Yes
Dimensions	218mm (L) x 75mm (W) x 43mm (D)
Weight	375g